



Power Eagle™ 716

specifications



Vacuum System	
Airflow at orifice	99 ft3 / 2.80m3
Vacuum motor amps	10.3 A
Vacuum motor hp	1.66 hp
Vacuum motor stages	3 stage
Vacuum motor voltage	120 V
Vacuum motor watts	1236 watts
Sealed waterlift	117 in / 2971.8 mm
Recovery System	
Recovery tank wet capacity	7 gal / 26.5 L
Pump System	
Solution pump amps	1 A
Solution pump pressure	100 lb psi / 45.36 kPa
Solution Delivery System	
Nominal solution flow rate	1 gpm / 3.78 L /min
Solution capacity	7 gal / 13.24 L
Solution flow quantity	1 gpm / 3.78 L /min
Spray jets	4 - quick disconnect
Brush Drive System	
Brush diameter	3.375 in / 87.5 mm
Brush length	13.5 in / 343 mm
Brush motor amps	1 A
Brush motor RPM	1800 rpm
Brush motor voltage	120 V
Brush motor watts	120 watts
Brush RPM	1200 rpm
Power System	
Power cord length	50 ft / 15.24 m
Power cord type	16 gauge
Amps	12.7 A
Voltage	120 V
Watts	1524 watts
Dimensions / Weight / Accessories	
Length	39 in / 990.6 mm
Width	16 in / 406.4 mm
Height	34 in / 863.6 mm
Net weight	86 lb / 39.01 kg
Sound level	77 dBA
Warranty	
	3 years / 2500 hrs on parts and labor (excluding batteries). 10 years on rotationally-molded polyethylene tanks.