



Power Eagle® specifications



	1016	1020
Vacuum System		
Vacuum motor hp		1.8 hp
Vacuum motor stages		3 stage
Brush Drive System		
Brush length	13 in / 330 mm	17 in / 432 mm
Brush diameter		3.31 in / 84 mm
Brush bristle type	Offset rows of nylon bristles in a chevron pattern	
Brush motor hp		0.25 HP
Brush motor RPM		2300 RPM
Brush motor amps		1.5 Amps
Brush RPM		1380 RPM
Solution Delivery System		
Solution pump pressure		100 psi / 690 kPa
Solution pump amps		1 A
Pump flow rate		1 gpm / 3.8 L / min
Solution capacity		10 gal / 38 L
Spray jets	Dual, quarter turn with large grip Electric solenoid	
Recovery System		
Sealed waterlift		136 in / 3450 mm
Airflow at 2 in orifice		95 ft ³ / min / 2.69 m ³ / min
Vacuum motor amps		13 A max
Recovery capacity		14.5 gal / 54.8 L
Power System		
Power cord length		50 ft / 15.2 m
Power cord description		16 gauge, safety yellow
Power consumption amps		14.5 A
Voltage		120 VAC
Watts		1740 W
Dimensions / Weight / Sound level		
Height	34 in / 864 mm	34 in / 864 mm
Length	43 in / 1092 mm	43 in / 1092 mm
Weight	98 lb / 44.8 kg	100 lb / 45.5 kg
Width	16 in / 406 mm	20 in / 508 mm
Sound level		78 dBA
Warranty	3 years/2500 hrs on parts and labor (excluding batteries). 10 years on rotationally-molded polyethylene tanks.	