



TrailBlazer® specifications



Vacuum System	TrailBlazer®	TrailBlazer® Lite	TrailBlazer® XP
Maximum coverage rate per hour	10,000 ft ² /h	10,000 ft ² /h	10,000 ft ² /h
Airflow at orifice	95 cfm / 2.7 m ³ /h	112 cfm / 3.2 m ³ /h	150 cfm / 4.2 m ³ /h
Waterlift at sealed orifice	92 in / 2337 mm	63 in / 1600 mm	100 in / 2540 mm
Vacuum motor hp	1.25 hp	1.1 hp	1.8 hp
Vacuum motor stages	2 – stage	1 – stage	1- stage
Debris Recovery System			
Vacuum bag capacity	6 quart	6 quart	9.8 quart
Vacuum bag description	Equipped with paper Intercept Micro Filter bag		
Vacuum bag filtration	Four-level Filtration™ 96.1% efficient at 1micron. Optional High Filtration Media Disc yields; 99.79% efficient at .3 microns		
Power System			
Power consumption amps	8.3 A	6.8 A	11.5 A
Voltage frequency	120 V / 60 Hz		
Power consumption watts	928 Watts	802 Watts	1340 Watts
Power cord length	50 ft / 15.2 m		
Power cord type	16 gauge; 3 wire SJTW, Safety Orange; detachable; UL listed		
Standard Equipment / Optional Accessories			
Standard equipment	1 ½" 5 ft / 1.5 m vacuum hose; 1 ½" 2-pc. Wand, E-Z Glide™ Multi-surface Floor Tool, Upholstery Tool, Crevice Tool, Dust Brush, shoulder straps and waist harness; detachable 50 foot / 15.2 m power cord with belt clip, reusable micro cloth bag and one paper Intercept Micro Filter vacuum bag.		
Optional accessories	Optional High Filtration Media Disc, air-driven turbo brush, 20" JetSweep™ hard floor tool, Sound Muffler for TrailBlazer only.		
Dimensions / Weight / Sound level			
Width	9 in / 229 mm	14 in / 356 mm	10 in / 254 mm
Height	23 in / 584 mm	15.5 in / 394 mm	25 in / 635 mm
Net weight	9 lb / 4.1 kg	7.5 lb 3.4 kg	11.5 lb / 5.2 kg
Depth	9 in / 229 mm	9 in / 229 mm	8 in / 203 mm
Sound level	68 dBA	68 dBA	70 dBA
Warranty	3 years/2500 hrs on parts and labor (excluding batteries). 10 years on rotationally-molded polyethylene tanks.		