



ESTEAM[®]

CLEANING SYSTEMS

OLEFIN PRESPRAY

Advanced formulation for Olefin carpets

Olefin Prespray is a specially developed concentrated pre-conditioner for Olefin (polypropylene) carpets. This scientific blend of surfactants and grease lifters removes oily and particulate soils that attract to Olefin carpet fibres.

- Dilution Ratio 1:45
- Designed for Olefin or commercial carpets
- Deep cleans oils and soil build-up
- Removes filtration soiling
- Reduces yellowing conditions
- Available in: 4 L (1.06 US gal), 20 L (5.28 US gal) or 205 L (54.1 US gal)

EASILY CUTS THROUGH OIL AND SOIL BUILD-UP

DIRECTIONS FOR USE:

Pretest in an inconspicuous location for color fastness and fibre stability.

Pump-up or Power Sprayer: Mix 3 oz (88.7 ml) of Olefin Prespray into 1 gal (3.78 L) of warm to hot water (1:45 Dilution).

Hydro-force™ Sprayer:

4:1 Dilution (No Tip) Mix 14 oz (413 ml) of Olefin Prespray into a Hydro-force™ jug and fill with warm to hot water.

8:1 Dilution (Yellow Tip) Mix 25 oz (737 ml) of Olefin Prespray

into a Hydro-force™ jug and fill with warm to hot water.

For best results: Pile lift or vacuum carpets prior to cleaning. Spray diluted Olefin Prespray solution onto carpet at a rate of 800 - 1,000 square feet per gallon (3.78 L). Agitate presprayed area using a mechanical brush or carpet groomer. Allow 15 minutes dwell time, then rinse with Esteam Fibre Rinse solution in conjunction with hot water extraction.

NOTE: Do not mix Esteam Olefin Prespray with any other chemical product.



Diluted pH: 10.0
Dilution Ratio 1:45

Keep this product out of reach of children. Read the Material Safety Data Sheet and the Product Label before using. Take the necessary precautions dictated by the label to ensure that your health and that of your customers' is protected.

Printed in Canada

